

● Content

5 - PROCESS - CALIBRATOR - HANDHELD - SIMULATOR

Page 1: Output: Voltage and current

Page 2: Output / input: Resistance thermometer and thermocouple

Page 3: Output: Resistance thermometer, thermocouple, resistance and voltage

Page 4: Output / input: Resistance thermometer and resistance

● Voltage and current (output)

Order number: PK00XXXX-XXX (without factory calibration certificate)
 PK01XXXX-XXX (with factory calibration certificate)
 PK02XXXX-XXX (with DKD calibration certificate, 1 measurand)



Characteristics

Output, range, accuracy: see table 1	
Battery supply:	9 V (ANSI/NFPA 1604A/IEC 6LR619V Alkaline)
Battery life:	approx. 12 hours at 10 mA
Maximum voltage:	30 V (between 2 terminals or 1 terminal and ground)
Ambient temperature:	operation: 0...50 °C / storage: -10...55 °C
Air humidity:	operation: maximum 80% rF / storage: maximum 90% rF
Dimensions:	200 x 100 x 40 mm (with carrying case)
Weight:	approx. 550 g (with carrying case)
Accessories:	manual, 1 set measuring cable
Standards:	according IEC1010 (EN61010)

Table 1 (valid for temperature range 18...28 °C up to 1 year after calibration)

Output	Range	Output range	Resolution	Accuracy	Notes
Voltage DC	10 V	0,000 up to 11,000 V	1 mV	±0,05% of set value ±2 mV	Maximum output current: 2 mA
Ampere DC	20 mA	0,000 up to 22,000 mA	0,001 mA	±0,05% of set value ±4µA	Maximum load: 1kΩ at 20 mA (see note 1)
Simulation Transmitter	-20 mA	0,000 up to -22,000 mA	0,001 mA	±0,05% of set value ±4µA	Maximum load: 1kΩ bei 20 mA
Current loop power	24 VDC			±10%	Maximum output current: 25 mA

Notes:

- 1) At a battery voltage of 6,8 V the maximum load is 1 kΩ at 20 mA. If the voltage is between 5,8 V and 6,8 V the maximum load is 700 Ω at 20 mA
- 2) Temperature coefficient: ±0,005% of range / °C in temperature ranges 0...18 °C and 28...50 °C

● Thermocouple and voltage (output and input)

Order number: PK20XXXX-XXX (without factory calibration certificate)
 PK21XXXX-XXX (with factory calibration certificate)
 PK22XXXX-XXX (with DKD calibration certificate, 1 measurand)



Output, input, range, accuracy: see table 1	
Battery supply:	9 V (ANSI/NFPA 1604A/IEC 6LR619V Alkaline)
Battery life:	approx. 12 hours at 10 mA
Maximum voltage:	30 V (between 2 terminals or 1 terminal and ground)
Ambient temperature:	operation: 0...50 °C / storage: -10...55 °C
Air humidity:	operation: maximum 80% rF / storage: maximum 90% rF
Dimensions:	200 x 100 x 40 mm (with carrying case)
Weight:	approx. 550 g (with carrying case)
Accessories:	manual, 1 set measuring cable
Standards:	according IEC 1010 (EN 61010)

Table 2 (valid for temperature range 18...28 °C up to 1 year after calibration)

Output	Range	Output range	Resolution	Accuracy	Notes
Voltage DC	100 mV	-10,00 up to 110,00 mV	0,01 mV	±0,05% of set value ±30 µV	Maximum output current: ±2 mA
	1000 mV	-100,00 up to 1100,00 mV	0,1 mV	±0,05% of set value ±0,3 mV	
Input	Range	Input range	Resolution	Accuracy	Notes
Voltage DC	100 mV	-10,00 up to 110,00 mV	0,01 mV	±0,05% of set value ±30 µV	Input resistance: 1 MΩ
Output / Input	Range	Output range / input range	Resolution	Accuracy	Notes
Thermocouple	Type R	-40 up to 1760 °C	1 °C	±0,05% of set value ±3 °C (values <100 °C)	Valid for ITS90 temperature tables (Input resistance for input signals: 1 MΩ) (see notes 1 and 2)
	Type S	-20 up to 1760 °C	1 °C	±0,05% of set value ±2 °C (values >100 °C)	
	Type B	400 up to 1800 °C		±0,05% of set value ±3 °C (values 400...600 °C) ±0,05% of set value ±2 °C (values >600 °C)	
	Type E	-200,0 to 1000,0 °C	0,1 °C	±0,05% of set value ±2 °C (values <-100 °C) ±0,05% of set values ±1 °C (values >-100 °C)	
	Type K	-200,0 to 1370,0 °C	0,1 °C		
	Type J	-200,0 to 1200,0 °C	0,1 °C		
	Type T	-200,0 to 400,0 °C	0,1 °C		
	Type N	-200,0 to 1300,0 °C	0,1 °C		

Notes:

- 1) The accuracy does not include the error of the internal temperature compensation for a sensor. The range of the internal temperature compensation is from 10 to 50 °C with a compensation error up to 0,5 °C.
- 2) Temperature coefficient: ±0,005% of range / °C in temperature ranges 0...18 °C and 28...50 °C

● Thermocouple, resistance thermometer, voltage and resistance (output)

Order number: PK30XXXX-XXX (without factory calibration certificate)
 PK31XXXX-XXX (with factory calibration certificate)
 PK32XXXX-XXX (with DKD calibration certificate, 1 measurand)



Characteristics

Output, input, range, accuracy: see table 3	
Battery supply:	9 V (ANSI/NFPA 1604A/IEC 6LR619V Alkaline)
Battery life:	approx. 12 hours at 10 mA
Maximum voltage:	30 V (between 2 terminals or 1 terminal and ground)
Ambient temperature:	operation: 0...50 °C / storage: -10...55 °C
Air humidity:	operation: maximum 80% rF / storage: maximum 90% rF
Dimensions:	200 x 100 x 40 mm (with carrying case)
Weight:	approx. 550 g (with carrying case)
Accessories:	manual, 1 set measuring cable
Standards:	according IEC1010 (EN61010)

Table 3 (valid for temperature range 18...28 °C up to 1 year after calibration)

Output	Range	Output range	Resolution	Accuracy	Notes
Voltage DC	100 mV	-10,00 up to 110,00 V	0,01 mV	±0,05% of set value ±30 µV	Maximum output current: ±2 mA
	1000 mV	-100,00 up to 1100,00 mV	0,1 mV	±0,05% of set value ±0,3 mV	
Resistance	400 Ω	0,0 up to 400,0 Ω	0,1 Ω	±0,05% of set value ±0,2 Ω	Ausgangsstrom ±1 mA (see notes 1 and 2)
Thermocouple	Type R	-40 up to 1760 °C	1 °C	±0,05% of set value ±3 °C (values <100 °C)	Valid for ITS90 temperature tables (see note 3)
	Type S	-20 up to 1760 °C	1 °C	±0,05% of set value ±2 °C (values >100 °C)	
	Type B	400 up to 1800 °C		±0,05% of set values ±3 °C (values 400...600 °C) ±0,05% of set value ±2 °C (values >600 °C)	
	Type E	-200,0 to 1000,0 °C	0,1 °C	±0,05% of set value ±2 °C (values <-100 °C) ±0,05% of set value ±1 °C (values >-100 °C)	
	Type K	-200,0 to 1370,0 °C	0,1 °C		
	Type J	-200,0 to 1200,0 °C	0,1 °C		
	Type T	-200,0 to 400,0 °C	0,1 °C		
Type N	-200,0 to 1300,0 °C	0,1 °C			
Resistance thermometer	Pt100	-200 up to 850 °C	0,1 °C	±0,05% of set value ±0,6 °C	Valid for PT100-385 (see notes 1 and 2)
	Cu50	-50,0 up to 150 °C	0,1 °C		

Notes:

- 1) without the corresponding lead resistance
- 2) range of exciting current: 0,5...2 mA, maximum voltage output <2 Volt
- 3) The accuracy does not include the error of the internal temperature compensation for a sensor. The range of the internal temperature compensation is from 10 to 50 °C with a compensation error up to 0,5 °C.
- 4) temperature coefficient: ±0,005% of range / °C in temperature ranges 0...18 °C and 28...50 °C

● Resistance thermometer and resistance (output and input)

Order number: PK10XXXX-XXX (without factory calibration certificate)
 PK11XXXX-XXX (with factory calibration certificate)
 PK12XXXX-XXX (with DKD calibration certificate, 1 measurand)



Characteristics

Output, range, accuracy: see table 4a	
Input, range, accuracy: see table 4b	
Battery supply:	9 V (ANSI/NFPA 1604A/IEC 6LR619V Alkaline)
Battery life:	approx. 12 hours at 10 mA
Maximum voltage:	30 V (between 2 terminals or 1 terminal and ground)
Ambient temperature:	operation: 0...50 °C / storage: -10...55 °C
Air humidity:	operation: maximum 80% rF / storage: maximum 90% rF
Dimensions:	200 x 100 x 40 mm (with carrying case)
Weight:	approx. 550 g (with carrying case)
Accessories:	manual, 1 set measuring cable
Standards:	according IEC 1010 (EN 61010)

Table 4a (valid for temperature range 18...28 °C up to 1 year after calibration)

Output	Range	Output range	Resolution	Accuracy	Notes
Ohms	400 Ω	0,0 up to 400,0 Ω	0,1 Ω	±0,05% of set value ±0,2 Ω	output current: ±1 mA (see notes 1 and 2)
Resistance thermometer	Pt100	-200,0 up to 850 °C	0,1 °C	±0,05% of set value ±0,6 °C	output current: ±1 mA table Pt100-385 (see notes 1 and 2)
	Cu50	-50,0 up to 150,0 °C	0,1 °C		output current: ±1 mA (see notes 1 and 2)

Table 4b (valid for temperature range 18...28 °C up to 1 year after calibration)

Input	Range	Output range	Resolution	Accuracy	Notes
Ohms	400 Ω	0,0 up to 450,0 Ω	0,1 Ω	±0,05% of set value ±0,2 Ω	measuring current: ±1 mA (see notes 1 and 2)
resistance thermometer	Pt100	-200,0 up to 850 °C	0,1 °C	±0,05% of set value ±0,6 °C	measuring current: ±1 mA table Pt100-385 (see notes 1 and 2)
	Cu50	-50,0 up to 150,0 °C	0,1 °C		measuring current: ±1 mA (see notes 1 and 2)

Notes:

- 1) without the corresponding lead resistance
- 2) range of exciting current: 0,5...2 mA, maximum voltage output <2 Volt
- 3) temperature coefficient: ±0,005% of range / °C in temperature ranges 0...18 °C and 28...50 °C