

Pressure measuring device with logger

GMH 3151




Special features:

- 4½-digit display probes with higher resolution up on request
- logger functions
- peak value memory
- analog output 0-1V
- 1000 measurements / second
- digital sensor adjustment possible
- min- / max-alarm
- integrated horn

Additional function of the GMH3156:

- 2 GMSD/MSD-probes connectable
- difference measurement of two probes

GMH 3156



GMH 3151 (probe not included)

GMH 3156 (probes not included)

GMH 3150 - ex (⊗ device without probe)

GMH 3156 - ex (⊗ device without probes)

NEW

suitable pressure probes page 22 / 23

Specification:	GMH3151	GMH3156	GMH3151-ex	GMH3156-ex
max. display range:	-19999 ... +99999 digit		-19999 ... +199999 digit	
Measuring range:	corresponding to used probe		corresponding to used probe	
Overload:	corresponding to used probe		corresponding to used probe	
Resolution:	corresponding to used probe		corresponding to used probe	
Accuracy: (device)	±0,1%FS ±1Digit (at nominal temperature = 25°C)			
Pressure units:	mbar, bar, Pa, kPa, MPa, mmHg, PSI, m, can be selected.			
Probe connection:	1	2	1	2
	6-pin screened lockable Mini-DIN-socket(s) for GMSD/MSD-sensors. Automatic probe detection and setting of meas. range upon plugging in of probe.			
Display:	2 x 4½-digit LCD		2 x 4½-digit LCD	
Output:	serial interface o. AAG		serial interface o. AAG*	
- serial interface:	direct connection to RS232 or USB interface of a PC via interface converter GRS3100, GRS3105 or USB3100 (accessories)		direct connection to RS232 or USB interface of a PC via interface converter GRS3100, GRS3105 or USB3100 (accessories)	
- analog output:	0-1V, freely adjustable (res. 12bit)		0-1V, freely adjustable (res. 12bit)	
Power supply:	9V-battery, d.c. connector suitable 9V-battery (type IEC 6F22) in scope of supply, d.c. connector for external 10.5-12V direct voltage supply. (suitable power supply: GNG10/3000)		9V-battery, d.c. connector*	
Sensor adjustment:	digital offset and scale input		digital offset and scale input	
Tare, hold, min/max value:	X	X	X	X
Peak value memory:	≥1 ms		≥1 ms	
Measuring cycle: "slow"	4 measurements / s		4 measurements / s	
"fast" (with filter)	≥ 1000 meas. / s		1000 meas. / s	
"peak-detect"	≥ 1000 meas. / s		1000 meas. / s	
Logger functions:				
manually data sets:	99		99	
-cycle data sets:	10000	4000	10000	4000
	(max. 64 recording sequences)		(max. 64 recording sequences)	
-adjustable cycle time:	1 ... 3600 seconds		1 ... 3600 seconds	
Averaging function:	X	X	X	X
Min-/max- alarm:	X	X	X*	X*
Real-time clock:	X	X	X	X
Power consumption:	max. 1.6mA (slow mode) max. 7mA (fast = 1000Hz)		max. 1.6mA (slow mode) max. 7mA (fast = 1000Hz)	
Working condition:	-25 to +50°C, 0 to +95%r.F. (non-condensing)		-10 ... 50°C, 0 ... 95 %RH (non-condensing)	
Power-Off-function:	1...120 min (can also be deactivated).			
Housing dimensions:	142 x 71 x 26 mm, impact-resistant ABS plastic housing. Front side IP65			
--	pop-up clip for table top or suspended use.			
Weight:	approx. 150 g		approx. 190 g (incl. case)	

* refer to note to EX-design types at page 20

General functional description:

Tare function: display value and the min./max values memorized can be set to zero.

Hold function: by pressing a button the current meas. value will be memorized.

Min./Max. value memory: memorizing of max. and min. values.

Peak value memory (peak-detect): In the min-/max-value memory will be detected not filtered pressure peaks or ≥1msec.

Averaging function: integrates the meas. values during a selectable period of time and then calculates the average display value.

Logger operation: Logger start and stop via the keyboard or interface. Comfortable read-out and display software (GSOFT3050) available as additional equipment.

Low power logger mode: (only in meas. cycle "slow") Only one measurement carried out at the end of the respective logger cycle. The battery life is considerably prolonged. For long-term recordings (eg. tightness).

Min-/Max-alarm: the measuring value is constantly monitored if they remain within the min./max. limits set (deaktivatable)

- Alarm: 3 different alarm settings

- "off" - alarm function deactivated
- "on" - visual alarm via display, interface alarm, alarm sounded via integrated horn.
- "no.So." - visual alarm via display and interface alarm

- Controlling function: with the help of the switching module GAM3000 (optionally) electric equipment can be switched on/off or alarm memoried (p.r.t. page 43)

SeaLevel-correction: when connecting an abs. pressure probe the barom. air press. can also be displayed corrected to sea level "zero". (Air pressure comp. achieved by entering the meters above sea level "zero")

Handheld instrument

Display / Controller

Logger / EASYBus

Transmitter

Temperature probe

Alarm / Protection